

AMENDMENTS TO THE SPECIFICATION

On page 11, lines 8-17 of the Application, as filed, please amend the paragraph as follows:

Figure 2 illustrates a conventional cleaning machine 13 which has machine sprayers 9 extending from the corners of the cleaning machine 13. These machine sprayers 9 are used as supply nozzles by the invention. In addition to the prior art cleaning machine 13, the additional features which comprise the invention are also shown in this figure. Holding devices 10 are shown installed at selected locations within cleaning machine 13. Likewise cleaning fluid extension tubes 11 are shown attached to machine sprayers 9 at their proximal end. The extension tubes 11 have nozzles 12 which are aligned with holding devices 10. The nozzles 12 and holding devices 10 are aligned such that when the components of a paint sprayer 1 are placed in holding devices 10, the nozzles 12 are ~~[[paint]]~~ pointed directly at the surfaces or apertures which require cleaning.

On page 13, lines 6-11 of the Application, as filed, please amend the paragraph as follows:

Figure 6A is a ~~close of~~ close up view of the paint sprayer body 2 held by holding device 10 in alignment with nozzles 12. This alignment allows the nozzles 12 to sprayer cleaning fluid directly into the appropriate apertures of paint sprayer body 2. By aligning nozzles 12 in this manner, the areas most in need of cleaning receive a directed flow of cleaning fluid to the controlled application of cleaning fluid provided by the holding devices 10 and the nozzles 12.

AMENDMENTS TO THE DRAWINGS

Fifteen sheets of drawings are attached. A complete set of formal drawings to replace the photographs from the application as filed, and an amended figure 7 which includes the legend: "Prior Art." A second set of drawings, marked in red, is included for the Examiner's convenience.